



में की पसंद















Patel Lubricant Pvt. Ltd.



About Company

Patel Lubricant Pvt. Ltd. markets a wide range of lubricating oils in the automotive, industrial and speciality segments under the brand name Pomson. Patel Lubricant Pvt. Ltd. offers lubrication solutions for a wide gamut of industrial and automotive applications. The Tribology & lubrication experts at Patel Lubricant Pvt. Ltd. have engineered and designed high quality products to suit unique and specific lubrication needs of all types of machines and automobiles. Consequently every lubrication solution from Patel Lubricant Pvt. Ltd. delivers exactly what it promises - the best quality product at the most reasonable price.

Higher efficiency Patel Lubricant Pvt. Ltd. are designed t ensure increased efficiency, reduced equipment maintenance and enhanced productivity, thereby delivering value to our customers. Driven by the passion for advanced technology, Patel Lubricant Pvt. Ltd. offers premium and cost effective lubricants grades which are carefully blended with high quality base oil and selected performance additives. The rigorous quality control procedures ensure delivery of superior and products which easily exceed the requirement of most stringent quality procedures. At Patel Lubricant Pvt. Ltd. you are never far for finding a unique and satisfactory solution to your entire lubrication needs.

The Team

Mr. Atul Patel (Chairman)

He is a B.Sc. Chemistry and comes with an overall experience of 21 years in the cosmetics industry. He along with the other founder members of Bollywood Multiplex Cinema Chain started under company Modern Moviee Pvt. Ltd. in the year 2000.

He has significantly contributed to the consistent growth of the company in both the domestic as well as international markets. With his active involvement in companies day to day activities in terms of Production and Advertisement, he has taken the company to a new level of success. His knowledge about the industry from the root levels has always allowed him to take Patel Lubricant Pvt. Ltd. to the heights.





Two Wheelers Engine Oil (20W40)

API SL / SM

Pomson 4T oil is a high performance 4 stroke motor cycle engine oil.

Premium multi-grade 4-stroke motorcycle engine oil specially formulated to provide year-round protection for 4-stroke motorcycle engines and is wet clutch compatible.



Pack Size: 900 ml • 1 L • 50 L • 210 L

Recommended for:

Honda • Hero • TVS Suzuki • BAJAJ • Yamaha • Mahindra





ENGINE OIL 10W30 / 10W40

API SN 4T Power Plus

- Vehicle Compatibility: All gearless vehicles and specifically compatible with Honda Activa, Dio and Access
- Special designed for fuel economy
- Reliable against wear and tear even under tough racing operating conditions
- Very good thermal resistance and stability



Pack Size: 800 ml • 900ml • 1 L • 50 L • 210 L

Recommended for:

Honda • Hero• TVS Suzuki • BAJAJ • Yamaha • Mahindra







BULLET ENGINE OIL (4T 15W50)

API SM JASO MA2

- Synthetic blend (Technosynthese) with ester 4-Stroke engine oil.
 Ester technology provides; improved shear resistance, smooth shifting and high temperature resistance
- Improved oil film resistance at high temperatures
- Meets JASO MA specifications for optimal wet clutch performance
- Viscosity: 15W50. Specifications: API SM JASO MA2



Pack Size: 2.5 L • 50 L • 210 L



CNG ENGINE OIL

- API SL/SM/20W50
- Vehicle Compatibility: All 2 & 4 stroke Bikes & Car Gasoline oil
- Excellent prevention against spark plug fouling and combustion chamber deposit formation
- Decreases oil consumption
- Prevention against exhaust port blocking and hence results in no power loss
- Very good thermal resistance and stability

Pack Size: 500ml • 1 L • 50 L • 210 L







DIESEL ENGINE OIL (15W40)

- Intelligent molecules cling to metal surfaces giving extra protection against engine wear
- Dedicated diesel technology maintains engine efficiency and responsiveness
- Provides excellent soot handling performance thus minimising oil thickening
- Exceeds the most demanding limits in the latest industry standard diesel protection test



API CF-4

Pack Size: 500ml • 1 L • 3 L • 3.5 L • 5 L• 7.5 L • 10 L

• 15 L • 20 L • 50 L • 210 L



API CF-4 / SL

Pack Size: 1 L • 3 L • 3.5 L • 5 L• 7.5 L • 10 L • 15 L

• 20 L • 50 L • 210 L



API CH-4 / SM

Pack Size: 1 L • 3.5 L • 5 L• 7.5 L • 20 L • 50 L • 210 L



PREMIUM TURBO PLUS

API CI-4+ / SM

Pack Size: 1 L • 3 L • 5 L• 7.5 L • 10 L • 15 L

• 20 L • 50 L • 210 L











DYNAMIC MULTI / CNG MULTI POWER

CF-4 / SF 20W40

- Comes with API SN specification, the highest motor oil standard or petrol vehicles and ACEA A3/B4 specification, making it ideal for fuel injected diesel engines
- Provides a smoother and guieter drive compared to mineral oils
- Reduces engine wear, especially in severe daily traffic conditions
- Reduces oil consumption which means there is a lesser need for top-ups
- Resists oil degradation and provides protection throughout the drain interval better than mineral oils

Pack Size: 1 L • 3 L • 5 L • 7.5 L • 10 L • 20 L • 50 L • 210 L









ULTRA POWER SYNTHETIC ENGINE OIL

API SN / CI-4+ 5W30 & 5W40 / 10W40

Pomson's synthetic blended motor oils meet and exceed the same specifications as these two products.

Pomson synthetic blended motor oils are high performing, highquality oils formulated with full synthetic base oils and top tier additives to provide an increased level of performance.



Pack Size: 1 L • 3 L • 3.5 L • 4 L • 5 L • 50 L • 210 L





GEAR OIL

API GL-4 ST-90 & GL-5 EP-90 / 140 / 320 / 460

Gear Oil is recommended for hypoid spiral bevel or worm gear transmission system of cars, buses, truck and tractors requiring EP 90 type lubricants. It gives smooth gear operations.

- Excellent thermal and chemical stability
- Protection against rust and corrosion ensuring longer and trouble free operation
- Standards: API GL-4 & GL-5
- Very good thermal resistance and stability.

Pack Size: 1 L • 5 L • 10 L • 20 L • 50 L • 210 L



GEAR OIL

API GL-5 80W90 / 85W140

Gear Oil is recommended for hypoid spiral bevel or worm gear transmission system of cars, buses, truck and tractors requiring 80W90/85W140 type lubricants. It gives smooth gear operations.

- Excellent thermal and chemical stability
- · Protection against rust and corrosion ensuring longer and trouble free operation
- Standards: API GL-5
- Very good thermal resistance and stability.

Pack Size: 1 L • 5 L • 10 L • 20 L • 50 L • 210 L









RADIATOR COOLANT

ANTI FREEZE 1:3 & 1:9

- Vehicle Compatibility: All Cars, trucks and tractor
- It lubricates the water pump and protects the engine from corrosive effects of water.
- Engine cool in extreme heat and retains liquid form even in Resist foaming, Improved corrosion protection for longer period, Improved hard water stability, Compatible with cooling system components, Hybrid technology coolant, Decreases oil consumption, Low foaming due to anti-foam properties.



Pack Size: 1 L • 3 L • 50 L • 210 L





- Smoother operation over a wide range of temperature
- Good cold start performance
- Strong anti-wear performance
- It ensures smooth gear changes, reduces friction, wear in extreme pressure, low temperature fluidity, good stability, thermal and oxidation resistance protecting against corrosion in operation
- Recommended for automatic transmission and power steering units of automobile and light trucks where original equipment manufacturer specifies Type A fluid
- It is also suitable for synchromesh gearbox



Pack Size: TQ Oil 500ml • 1 L • 5 L | FORK Oil 175ml • 350ml







GREASE GEL RED

NLGI 3

- Premium quality High Drop Point
- Provides service for 75000 km or more under ideal operating conditions
- Fortified with EP additive for severe service condition
- Maximum lubricant with protection
 Excellent water resistance
- Protection against rust & corrosion



Recommended for

Cars, Trucks, Buses, Heavy Vehicle & All type of Farm and Industrial Machinery

Pack Size: 100gm • 250 gm • 500 gm

1 Kg • 2 Kg • 3 Kg • 5 Kg • 18 Kg • 180 Kg





GREASE ALL WHETHER - CALCIUM / POWDER BASE

AW - 3 / AP - 3

- Premium quality multipurpose automotive and general purpose grease
- · Resistance to water washout; retains grease in wet environment
- Effective oxidation inhibitor reduces the degradation of the base oil in service; increasing the service life of the grease.
- Mechanical stability minimises sheer down of the grease; reducing leakage from bearings
- A lithium based grease, provides maximum protection against heat, rust and corrosion
- Resists melt down at higher temperatures and highly resistant to water.

Pack Size: 250 gm • 500 gm • 1 Kg • 18 Kg • 180 Kg









Pure Blue DEF (Diesel Exhaust Fluid)

AUS 32

Pomson DEF I essential for the correct operation of Selective Catalyst Reduction (SCR) exhaust systems installed in BS-IV & BS-VI diesel vehicles in order to reduce NOx concentrations in emissions. It's a non-toxic, non-polluting an on-hazardous liquid.

Benefits: Protection for SCR • Prevents fouling/clogging of spray nozzles • Prevents gummy deposits in the tail pipe • Improves fuel economy • Convert NOx pollution to nitrogen and water • Environment friendly • Lower operating cost

Note: It should be stored in covered conditions, below 60° and above -11°c. Protect it from Dirt, Oil or any other contaminants after open the seal. Store it in proper storage facility. Do not add DEF in fuel tank.

Pack Size: 10 L • 20 L • 50 L • 210 L







SAE80 (Universal Tractor Transmission Oil (UTTO))

A premium quality Universal Tractor Transmission Oil (UTTO) formulated from high quality hydrotreated base stocks and carefully selected additives, designed to deliver the best performance in transmission, hydraulic, final drive and PTO systems of modern tractors.

Benefits: Balanced lubricity and other functional properties. Minimizes clutch-plate wear and brake chatter. Provides excellent lubrication for gear box and transmission equipment. Minimizes wear in high pressure hydraulic pump systems. Superior protection against Rust and Corrosion.

Pack Size: 1 L • 5 L • 7.5 L • 10 L • 20 L







INDUSTRIAL GRADE OIL

- 1. Hydraulic Oil AW 32/46/68
- 2. Gear Oil EP 90/140/220/320/460
- 3. Soluble Cutting Oil 1:20/1:30
- 4. Conning Oil for Textile
- 5. Transformer Oil
- 6. Rubber Process Oil
- 7. Machine Oil
- 8. Spindle Oil
- 9. Turbine Oil
- 10. Air Compressor Oil
- 11. White Oil

Pack Size: 50 L • 210 L



HYDRAULIC OIL

AW/68 - AW/46 - AW/32 - AW/10, MTB, HLP

- System oils are premium quality anti wear type lubricants formulated with superior quality of hydro treated base stock
- They provide long service life and are recommended for hydraulic and circulation systems of wide variety of equipments
- These oils are also used for compressor crankcase lubrication, but are not recommended for lubrication of turbines and equipments having silver coated components.

Pack Size: 5 L • 10 L • 20 L • 26 L • 50 L • 55 L • 210 L









RECOMMENDATION OF CAR

TATA

Indica P	4 Ltr
Indigo P	4 Ltr
Indica D	5.5 Ltr
Indigo D	5.5 Ltr
Marina D	5.5 Ltr
Vista D	5.5 Ltr
Indica ECS/Dicor	5.5 Ltr
Safari Oil D	7.5 Ltr
Safari Dicor Strom	7.5 Ltr
Sumo Spacio	7.5 Ltr
Nano P	2.5 Ltr
Indica Vista	3.3 Ltr
Manza D	3.3 Ltr
Vista P	2.6 Ltr
Manza P	2.6 Ltr
Nexon D	6.5 Ltr
Nexon P	5.5 Ltr
Tigor P	3.5 Ltr
Tigor D	4 Ltr
Tiago	3.5 Ltr
Altroz	3.5 Ltr
Harrier	5 Ltr
E18/00 / E18/40 / C	014/40

5W30 / 5W40 / 20W40 15W40 / 20W50 EP-90 / 80W90

MARUTI

Wagonr	2.9 Ltr
Dzire	3.1 Ltr
Eco Petrol	4.2 Ltr
Alto	3 Ltr
S-Presso	2.8 Ltr
Brezza	3.2 Ltr
Ertiga	3.2 Ltr
Celerio	3.4 Ltr
Baleno	3.1 Ltr
XI-S	3.1 Ltr
Swift	3.6 Ltr
Ciaz	3.2 Ltr
Ignis	3.8 Ltr
S-Cross	3.1 Ltr
Omni-800	3.0 Ltr
Sx4 D	4.3 Ltr
Ertiga D	3.2 Ltr
Dzire D	3.2 Ltr
Ritz D	3.2 Ltr
5W30 / 5W40 / 20W40 15W40 / 20W50 EP-90 / 80W90	

HYUNDAI

Tucson Kona	4.8 Ltr
Elentra	4.2 Ltr
Creta	4.8 Ltr
Venue	3.6 Ltr
Grand I-10	3.5 Ltr
Verna	3.3 Ltr
Aura	3.6 Ltr
Santro	3.1 Ltr
G-I 10 Nios	3.6 Ltr
I-20 3.6 Ltr	
5W30 / 5W40 15W40 / 20W50 EP-90 / 80W90	

NISAAN

Sunny P	3 Ltr
Micra P	3 Ltr
Evalia P	3 Ltr
Sunny D	4.5 Ltr
Micra D	4.5 Ltr
Evalia D	4.5 Ltr
5W30 / 5W40 / 20W40 15W40 / EP-90 / 80W90	
15W40 / EP-90 / 80W90	

TOYOTA

Yaris	3.2 Ltr
Camry	4.4, 5 Ltr
Fortuner	5.6 Ltr
Vellfire	4.3 Ltr
Chrysler	5.9 Ltr
Inova D	6.9 Ltr
Inova P	5.9 Ltr
Etios P	2.9 Ltr
Etios D	3.9 Ltr
Corolla P	4.0 Ltr
Corolla D	4.2 Ltr
Qualis D	5.0 Ltr
Liva P	2.9 Ltr
Liva D	3.9 Ltr
EW30 / EW40	

5W30 / 5W40 15W40 / 20W50 EP-90 / 80W90

FIAT

Punto P	3.2 Ltr
Punto	3.5 Ltr
Linea D	3.5 Ltr
Linea P	3.2 Ltr
=14/00 /=14/40	

5W30 / 5W40 15W40 / 20W50 EP-90 / 80W90

SEGMENT BY POMSON LUBRICANTS

HONDA

Civic	3.7, 4 Ltr
CR-V	3.7, 4 Ltr
Honda City	3.7 Ltr
WR-V	3.2 Ltr
Jazz	3.7 Ltr
Amaze P	3.2 Ltr
Amaze D	4.2 Ltr
Accord	4.5 Ltr
BR-V P	4 Ltr
5W30 / 5W40 / 20W40	

VOLKSWAGAN

15W40 / 20W50 EP-90 / 80W90

Polo P	2.8 Ltr
Polo D	4.3 Ltr
Vento D	4.3 Ltr
T-Roc	5 Ltr
Tiguan	4 Ltr
Jetta	4 Ltr
Passat	4 Ltr
Tourang	8 Ltr
Betle	8 Ltr

5W30 / 5W40 0W40 / 80W90

MAHINDRA

Thar	6.5 Ltr
XUV 300 P	4 Ltr
XUV 300 D	6 Ltr
Bolero	6 Ltr
XUV 500	6 Ltr
Xylo	6 Ltr
KUV 100 NXT	4 Ltr
Verito D	3.5 Ltr
Scorpio	7 Ltr
Logan	4 Ltr
Verito	4 Ltr

5W30 / 5W40 / 20W40 15W40 / 20W50 EP-90 / 80W90

FORD

Mustang	5.4 Ltr
Eco-Sport D	4.2 Ltr
Ford Figo	3.8 Ltr
Aspire	3.5 Ltr
Freestyle	3.5 Ltr
Endeavor	6.6 Ltr
5W30 / 5W40 / 15W40	

EP-90 / 80W90

SKODA

5W30 / 5W40 0W40 / 80W90	
Laura	4.3 Ltr
Fabia	3.8 Ltr
Rapid D	4.3 Ltr
Rapid P	3.5 Ltr
Superb	3.5 Ltr
Octavia	3.8, 4.3 Ltr

RENAULT

5W30 / 5W40 / 15W40 FP-90 / 80W90	
Pulse Scala D	4.5 Ltr
Duster P	4.5 Ltr
Pulse Scala P	3.0 Ltr
Duster (D)	4.5 Ltr
Kwid	2.5 Ltr

MITSUBISHI

7.5 Ltr	
4 Ltr	
4 Ltr	
5W30 / 5W40 / 15W40 EP-90 / 80W90	

MERCEDES

C - Class	6.5 Ltr
A - Class	4.5 Ltr
G - Class	7 Ltr
S - Class	8 Ltr
E - Class	5.5 Ltr
Benz GLA	5.8 Ltr
GLC - Class	7.2 Ltr
GLE	7.9 Ltr
GLS	4.8 Ltr
AMG GT	7.2 Ltr
GLE Coupe	7 Ltr
Benz Maybech	6 Ltr
Class Cabriolet	7.5 Ltr
CLS Coupe	8 Ltr

5W30 / 5W40 0W40 / 80W90

VOLVO

XC-60	6.5 Ltr
XC-40	6.5 Ltr
XC-90	5.5 Ltr
V90	6.5 Ltr
S90	6.5 Ltr
5W30 / 5W40 0W40 / 80W90	

BMW

3 Series	4.25 Ltr	
XS BMW	6.5 Ltr	
X1 BMW	5 Ltr	
X3 BMW	6.5 Ltr	
X6 BMW	8.5 Ltr	
BMW S-Series	4.25 Ltr	
X7 BMW	5 Ltr	
Z4 BMW	4 Ltr	
BMW Z-Series	7 Ltr	
BMW Z-Series	6 Ltr	
X4	4.8 Ltr	
Series 8	6.5 Ltr	
Series 6	6.5 Ltr	
5W30 / 5W40		

5W30 / 5W40 0W40 / 80W90

AUDI

A4	6.1 Ltr
A5	6.1 Ltr
A6	7 Ltr
A8	6.1 Ltr
A8L	7.6 Ltr
RS7	8.3 Ltr

5W30 / 5W40 0W40 / 80W90



Splendor CD 100 Joy CD Dawn Passion

Street

Achiever

CBZ Xtreme

Hunk

Impulse Glamour

Ambition

Pleasure

Maestro

RECOMMENDATION OF 2 WHEELERS

Scooly
Pep
Streak
Teenz
Victor
Phoenix 125
Spectra
Sport
Star
Star City
Star Sport
Centra
Flero
F2
Flame
Victor GLX
Edge 125
Apache 150
Wego
Jive
Flame
Super Champ
Euro Champ
Samurai
Shaolin

Shogun

Jupiter

BAJAJ

DAUAU
Boxer
Calibre 110 / 115
Croma
Kavasaki 4S
Champion
Aspire 112
Safire
Discover
Pulsar
CT 100
Platina
Eliminator
Avenger
Chetak
Sunny
Spirit
Spice
Rave

LML

Energy
Adreno
Freedom
Prima
Topper
Executive
Graplor
Beamer
CRD 100
Pulse
Star XP
Select
Supramo
Prithvi

HONDA Activa

Activa
Dio
Aviator
Eterno
Shine
Twister
Stunner
Yuga
Dream Neo
Unicorn
Dazzler
CB Trigger
CBR 250R

SUZUKI

Duro

Kine

Centuro

YAMAHA

Enticer
Gladiator
Fazer
RX 100 / 135
RXZ
RXG
Libero
Crux
YZF
R15
Fascino
RAYZR

4T - 5W30

4T - 5W40

4T - 10W30

4T - 10W40

4T - 10W50

4T - 15W50

4T - 20W40

4T - 20W50

RANGE OF ALL GRADES

API SL / SM / SN & FULLY SYNTHETIC





Patel Lubricant Pvt. Ltd.

Regd. Office: Annapurna Building, New Link Road, Andheri (W). Mumbai - 400 053. E: sales@pomson.in W: www.pomson.in

Customer Care (Toll Free): 1800 572 2129

Factory: Plot No.6, Block No. 449/A, Baleshwar Ind. Estate, National Highway 8, Palsana, Surat - 394317.

